



2780 Waterfront Pkwy. E. Dr. Suite 200 Indianapolis, IN 46214
 Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.
 Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **AMBER PET USP**
 Revised **05/20/2014**
 HazMat Name: **Non-Regulated**

Product Code: **PEN1820-00-C-DR**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
ORGANIC ACIDS	P/F	USP	PASS		PASS
VISCOSITY @ 210°F	SUS	D2161			66.7
API GRAVITY		D1298			30.2
SPECIFIC GRAVITY @ 60/25°C		D1298	.8150	.8550	.8494
COLOR, LOVIBOND, RED		IP 17		7.0	2.0
COLOR, LOVIBOND, YELLOW		IP 17		35.0	30.1
COLOR, PETROLATUM	P/F	USP	PASS		PASS
RESIDUE ON IGNITION	%	USP		.1	0.0
CONSISTENCY	dmm	USP	175	205	183
FIXED OILS, FATS, ROSINS	P/F	USP	PASS		PASS
ACIDITY	P/F	USP	PASS		PASS
ALKALINITY	P/F	USP	PASS		PASS
MELTING POINT	°F	USP CLSIII	125.0	135.0	132.1

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.